



CH07 | CH10 | CH14 | CH16 CH21

6" Channel Tandem Axle Carhauler

7,000 - 21,000 Lb GVWR

Stock photo. May be shown with additional options.



Available Sizes

LENGTH	WEIGHT	LENGTH	WEIGHT
83" X 12'	2,305 lbs.	102" X 12'	*
83" X 14'	2,456 lbs.	102" X 14'	*
83" X 16'	2,624 lbs.	102" X 16'	*
83" X 18'	2,783 lbs.	102" X 18'	*
83" X 20'	2,945 lbs.	102" X 20'	*
83" X 22'	3,153 lbs.	102" X 22'	*
83" X 24'	3,723 lbs.	102" X 24'	*
83" X 26'	3,881 lbs.	102" X 26'	*

*Base Weight Estimate Only

*Some sizes not available with different axle ratings.

*Lengths available up to 40FT.

Deck Height - 24"



MAX-RAMPS AVAILABLE



TRIPLE AXLE AVAILABLE



17 COLORS AVAILABLE

STANDARD SPECIFICATIONS

*listed specs based on CH14 base model

- 14,000 lb GVWR
- 7,000 lb GAWR (ea. axle)
- 6" Channel Tongue
- 6" Channel Frame
- 3" Channel 16" OC Cross-members
- (2) 7,000 lb Dexter Elec/Spring Axles (Forward Self Adjust)
- 15" 5-Hole Wheels w/ ST205/75 R15 LRC Tires
- Multi-Leaf Spring Suspension
- (1) 10,000 lb Drop-Leg Jack
- 2-5/16" Adjustable Coupler
- Straight Deck w/5' Slide-In Ramps
- Removable Diamond Plate Fenders
- (4) 3" Standard D-Rings
- 2" X 2" x 1/8" Tubing Front Rail
- 2" x 2" x 3/16" Angle Iron Uprights (Front Rail)
- (2) - Safety Chains
- Treated Pine Flooring
- LED Lighting
- 16 Ga. 5-Way Double-Insulated Harness w/7-way Plug & Front Polar Cord
- Mechanical and/or Chemical Pretreatment for Maximum Paint Adhesion
- Black - Sherwin-Williams Powdura OneCure Primer w/Polyester TGIC Gloss Powder Topcoat

AXLE OPTIONS

- (2) 3,500 Lb Dexter 2 Elec/Spring (FSA)
- (2) 5,200 Lb Dexter 2 Elec/Spring (FSA)
- (2 or 3) 7,000 Lb Dexter 2 Elec/Spring (FSA)
- (2) 8,000 Lb Dexter 2 Elec/Spring (FSA)

COUPLER OPTIONS

- 2" Adjustable BP Coupler
- 2-5/16" Adjustable BP Coupler (6-Hole)
- 3" Adjustable Pintle Ring (6-Hole)

GATES DOVETAILS, & RAMPS

- 2', 3', or 4' Dove Tail
- (2 or 3) 5' Fold-Up Ramps
- 6' Slide-In Ramps
- 4', 5', or 6' Heavy Duty Fold-up Gate
- 4', 5' or 6' Heavy Duty Split Fold-Up Gate
- 6' Stand-Up Ramps w/ Center Gate
- Double Hinges For Ramps
- MAX-Ramps

OTHER OPTIONS

- ST225/75 R15 LRD Tires
- ST235/85 R16 LRG Tires
- 8" Channel Frame
- Steel Diamond Plate Floor
- Rough Oak Floor
- Douglas Fir Floor
- Blackwood Floor
- 12" OC Cross-Members
- Aluminum Fenders
- Steel Diamond Plate Fenders
- Drive-over Fenders
- 7K Drop-Leg Jack
- (1 or 2) 10K Drop-Leg Jack(s)
- 3" or 4" additional d-rings (weld-on, bolt-on, recessed or removable)
- Tongue-Mount Toolbox w/Gas Shock
- Spare Tire & Mount (removable or weld-on)
- Rear Support Stands (tubes or jacks)
- Additional Stake Pockets
- Receiver Hitch
- Running Boards
- 2" Rub Rail
- 9.5K, 12K, or 17.5K Winch Package
- Winch Plate

NOTES

Axles available in straight, drop or torsion, with electric or hydraulic brakes. Drive-over fenders standard on 102" wide carhaulers. 8" Channel Frame & Dual 10K jacks standard on 24 ft.+ Length carhaulers. 18 ft. & up come with rear slide-in ramps. Side Rails can be removable or weld-on. Aluminum fenders available with 3.5K & 5.2K axle options only.

