

# PALLET FORKS

RAIL | HEAVY DUTY



JOHN DEERE



# Pallet Forks

RAIL | HEAVY DUTY



## Specifications

- Quik-Tatch™ system allows easy hook-up in seconds.
- Rail-style pallet forks are available in 1067-mm (42 in.) and 1219-mm (48 in.) lengths, heavy duty in 1219-mm (48 in.) length.
- Skid-resistant steps on both sides of the pallet-fork frame ease entrance and exit.
- Rail style holds forks in a rigid position and features a single-piece backrest and unrestricted visibility to the fork tips. Forks can be positioned in 203–1016-mm (8–40 in.) wide in 102-mm (4 in.) increments. Heavy-duty forks can be positioned in 203–1524-mm (8–60 in.) wide in 102-mm (4 in.) increments.
- Like all Worksite Pro™ attachments, these pallet forks are optimized to work with John Deere G- and E-Series Skid Steers and Compact Track Loaders (CTLs), and K- and J-Series Compact Wheel Loaders, and are compatible with most competitive models. See your local John Deere dealer for details.

|                                    | RAIL                                                                                                   | HEAVY DUTY                                                                                                                        |
|------------------------------------|--------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| <b>Frame Width</b>                 |                                                                                                        |                                                                                                                                   |
| With Steps                         | 1353 mm (53.3 in.)                                                                                     | 1723 mm (67.8 in.)                                                                                                                |
| Less Steps                         | 1149 mm (45.3 in.)                                                                                     | 1524 mm (60.0 in.)                                                                                                                |
| Frame Height                       | 986.5 mm (39 in.)                                                                                      | 977 mm (38.5 in.)                                                                                                                 |
| <b>Frame and Fork</b>              |                                                                                                        |                                                                                                                                   |
| <b>Overall Length</b>              |                                                                                                        |                                                                                                                                   |
| 1067 mm (42 in.)                   | 1251 mm (49.3 in.)                                                                                     | N/A                                                                                                                               |
| 1219 mm (48 in.)                   | 1403 mm (55.3 in.)                                                                                     | 1460 mm (57.5 in.)                                                                                                                |
| <b>Overall Weight</b>              |                                                                                                        |                                                                                                                                   |
| 1067 mm (42 in.)                   | 180 kg (397 lb.)                                                                                       | N/A                                                                                                                               |
| 1219 mm (48 in.)                   | 184 kg (407 lb.)                                                                                       | 273 kg (602 in.)                                                                                                                  |
| Fork Thickness                     | 35 mm (1.4 in.)                                                                                        | 45 mm (1.78 in.)                                                                                                                  |
| Pallet Fork Rating (pair of tines) | 1700 kg (3,750 lb.)                                                                                    | 2270 kg (5,000 lb.)                                                                                                               |
| Vehicle Compatibility              | 312GR, 314G, 316G, 318G/E, 326E, 328E, and 332E Skid Steers; and 317G, 319E, 323E, 329E, and 333E CTLs | 326E, 328E, and 332E Skid Steers; 317G, 319E, 323E, 329E, and 333E CTLs; and 204K, 244K/J, 304K, and 324K/J Compact Wheel Loaders |

**WORKSITE PRO™**

This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

