

RTX450

RIDE-ON TRACTOR



MANEUVERABILITY. A class-leading compact turning diameter allows the RTX450 to perform in narrow jobsites – especially in residential areas.



IN CONTROL. A common control system across the entire RTX lineup can help improve operator efficiency when operating Vermeer ride-on tractors.



THE PRODUCTIVITY DIFFERENCE. Experience a productivity difference due to a 14% increase in horsepower (as compared to the RT450), while the Tier 4 Final or Interim compliant engine allows you to meet local emissions requirements.



MEET YOUR JOBSITE STANDARDS. With a 26" (66 cm) tire standard-duty axle option, and the 29" (73.7 cm) tire and industry-exclusive quad track heavy-duty axle options, choose the configuration that works best for your jobsite requirements.



MAKE SENSE OF YOUR TRENCH. When difficult conditions are encountered while trenching causing a sudden drop in engine speed, the TrenchSense™ feature automatically pauses the forward motion of the tractor to prevent engine shutdown and recalibration of the machine controls. Once pre-set engine and trencher speed recovers, forward AutoCreep resumes. The sequence occurs within seconds and requires no operator adjustment.



GROUND DRIVE POWER. An electronically controlled hydraulic pump provides operators with more precise control and greater efficiency in comparison to machines with manually controlled pumps.

RTX450 RIDE-ON TRACTOR

GENERAL WEIGHTS AND DIMENSIONS

Weight [basic tractor, 26" (66 cm) tire]: 4575 lb (2075.2 kg)

Weight [basic tractor, 29" (73.7 cm) tire]: 4720 lb (2141 kg)

Weight (basic tractor, tracks): 6205 lb (2814.5 kg)

Length (basic tractor, tires): 109" (276.9 cm)

Length (basic tractor, tracks): 114" (289.6 cm)

Width (basic tractor, tires): 60" (152.4 cm)

Width (basic tractor, tracks): 64" (162.6 cm)

Height [basic tractor, 26" (66 cm) tire]: 88.7" (225.3 cm)

Height [basic tractor, 29" (73.7 cm) tire]: 90.3" (229.4 cm)

Height [basic tractor, tracks]: 92.6" (235.2 cm)

Tread width [26" (66 cm) tire, centerline to centerline]: 48" (121.9 cm)

Tread width [29" (73.7 cm) tire, centerline to centerline]: 50" (127 cm)

Tread width (tracks, centerline to centerline): 48.8" (124 cm)

Ground clearance [26" (66 cm) tire]: 7.4" (18.8 cm)

Ground clearance [29" (73.7 cm) tire]: 9" (22.9 cm)

Ground clearance (tracks): 9.85" (25 cm)

Wheel base (centerline of axles): 48" (121.9 cm)

Roll-over protective structure (2-post ROPS): 10,500 lb (4762.7 kg)

ENGINE

Make and model: Deutz 2.9L D Tier 4 Final

Noise level at operator's ear: 92.2 dB(A)

Manufacturer's gross hp rating: 49 hp (36.5 kW)

Max torque: 108 ft-lb (146.4 Nm)

Cooling medium: Liquid

Fuel type: Ultra-low sulfur diesel

Emissions rating: Tier 4 Final (EU Stage IIIA)/Tier 4i (EU Stage IIIB)

CAPACITIES

Fuel tank: 17.6 gal (66.6 L)

Hydraulic tank: 13 gal (49.2 L)

Hydraulic system: 14.8 gal (56 L)

Coolant: 1.7 gal (6.4 L)

GROUND DRIVE - RUBBER TIRE OPTION ONE

Max transport speed (fwd/rev in high): 3.7 mph (6 km/h)

Max creep speed (fwd/rev in low): 1.9 mph (3.1 km/h)

Tire size: 26" (66 cm) x 12" (30.5 cm)

GROUND DRIVE - RUBBER TIRE OPTION TWO

Max transport speed (fwd/rev in high): 3.8 mph (6.1 km/h)

Max creep speed (fwd/rev in low): 2.1 mph (3.4 km/h)

Tire size: 29" (73.7 cm) x 12.5" (31.8 cm)

GROUND DRIVE - TRACKS

Max transport speed (fwd/rev in high): 2.3 mph (3.7 km/h)

Max creep speed (fwd/rev in low): 1.5 mph (2.4 km/h)

Track contact length: 25.5" (65 cm)

Track width: 14" (35.6 cm)

AXLE OPTIONS

Front axle type: Steerable and oscillating 68/80 series planetary axles

Rear axle type: Rigid and steerable 68/80 series planetary axles

Axle load rating (static, 68 and 80 axles): 14,837 lb (6730 kg)

Outside turning diameter [26" (66 cm) and 29" (73.7 cm) tires, front steer only]: 23.8' (7.3 m) and 30.3' (9.2 m)

Outside turning diameter (tracks, front steer only): 28.5' (8.7 m)

Outside turning diameter [26" (66 cm) and 29" (73.7 cm) tires, front and rear steer]: 12.9' (3.9 m) and 16.5' (5 m)

Outside turning diameter (tracks, front and rear steer): 16.7' (5.1 m)

Service brake type: Hydraulic

Parking brake type: Mechanical hand break

ATTACHMENT OPTIONS

Front Options:

Backfill blade

Backhoe

Porta Bore

Reel carrier

Back options:

Center mount trencher

Plow

Sliding offset trencher

For more information on attachments, visit Vermeer.com